

VEGA 2D Super / VEGA 2D • hot-dip galvanized

Panel made of spot-welded steel bars.
 Anti-corrosion protection: hot-dip galvanized. Horizontal (double) wire diameter:
 VEGA 2D Super: 2x8 [mm], VEGA 2D: 2x6 [mm].
 Vertical wire diameter: VEGA 2D Super: 5.9 [mm], VEGA 2D: 4.8 [mm].
 Straight mesh size: 50x200 [mm].
 Panel width, edge bar centre to centre: 2500 [mm].
 Top finish: vertical bars, length: 30 [mm].

VEGA 2D Super / VEGA 2D • galvanized + PE coating

Panel made of spot-welded steel bars.
 Anti-corrosion protection: galvanized + PE coating.
 Horizontal (double) wire diameter: VEGA 2D Super: 2x8 [mm], VEGA 2D: 2x6 [mm].
 Vertical wire diameter: VEGA 2D Super 6 [mm], VEGA 2D: 5 [mm].
 Straight mesh size: 50x200 [mm].
 Panel width, edge bar centre to centre: 2500 [mm].
 Top finish: vertical bars, length: 30 [mm].



Fig. 39. VEGA 2D welded mesh panel fence.

OMEGA post

Hot-dip galvanized or galvanized + PE coating.
 Post cross section: 60x40x1.5 [mm], Post, H=3200 [mm] - 60x40x2 [mm].
 The post is complete with a plastic top cap (available colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts).
 Anti-corrosion protection: hot-dip galvanized or galvanized + PE coating.



Fig. 40. Omega post: standard clamp.



Fig. 41. Omega post: D1 clamp.



Fig. 42. Omega post: D2 clamp.

Delta post

Hot-dip galvanized or galvanized + PE coating.
 Post cross section: 60x40x1.5 [mm], Post, H=3200 [mm] - 60x40x2 [mm].
 The post is complete with a plastic top cap (available colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts). Also available as a corner post.
 Anti-corrosion protection: hot-dip galvanized or galvanized + PE coating.

Type S

The post features installation brackets in standard quantity (see the price table). Available bracket colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts.

Type L

The post features mounted installation consoles under each double wire row (see the price table). Available bracket colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts.



Fig. 43. Delta post

Sigma post

Hot-dip galvanized or galvanized + PE coating.
 Post cross section: 60x40x1.5 [mm], Post, H=3200 [mm] - 60x40x2 [mm].
 The post is complete with a plastic top cap (available colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts). Also available as a corner post.
 Anti-corrosion protection: hot-dip galvanized or galvanized + PE coating.

Note: The system is available in kits only (post + accessories).

Type L

The post features mounted installation consoles under each double wire row (see the price table). Available bracket colours: RAL 6005 (green), RAL 7016 (ash), RAL 9005, RAL 7040 (light grey) - on galvanized posts.

Note: The system is available in kits only (post + accessories).



Fig. 44. Sigma post