

VEGA B Light II

Panel made of spot-welded steel bars (single horizontal and vertical bars).

Anti-corrosion protection:

- hot-dip galvanized,
- galvanized + PE coating.


Wire diameter: 3.0 [mm].

Straight mesh size: 80x100 [mm].

Small mesh size: 80x50 [mm].

Panel width, edge bar centre to centre: 2500 [mm].

Top finish: vertical bars, length: 30 [mm].



Omega 40 post

- Post cross section: 40x1 [mm].
- The post is complete with a plastic top cap (RAL 9005 (black)).
- Anti-corrosion protection: hot-dip galvanized, galvanized+ PE coating.



Fig. 28. Omega 40 post

Gamma post

- Post cross section: 65x42 [mm].
- The post features installation holes.
- The post is complete with a plastic plug (RAL 9005 (black)).
- Anti-corrosion protection: galvanized + PE coating.
- Accessories available in: RAL 6005 (green), RAL 7016 (ash).



Fig. 29. Gamma post.

Omega 48 post

- Post cross section: 48.3x1.5 [mm].
- The post is complete with a plastic top cap (RAL 9005 (black)).
- Anti-corrosion protection: hot-dip galvanized or galvanized + polyester coating.



Fig. 30. Omega 48 post

Omega post

- Post cross section: 60x40x1.5 [mm], Post, H=3200 [mm] - 60x40x2 [mm]
- The post is complete with a plastic top cap (available colours: RAL 6005 (green), RAL 7016 (ash), RAL 7040 (light grey) - on galvanized posts).
- Anti-corrosion protection:
- hot-dip galvanized or galvanized + PE coating.



Fig. 31. Omega post: standard clamp.



Fig. 32. Omega post: D1 clamp.



Fig. 33. Omega post: D2 clamp.